

(19)

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 853 931 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
22.07.1998 Bulletin 1998/30

(51) Int. Cl.⁶: A61F 2/36, B21D 41/02,
A61F 2/46

(21) Application number: 97122707.9

(22) Date of filing: 22.12.1997

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Orsi, Stefano
Jardin Vitoria Regia 05657080, Sao Paulo-SP
(BR)



(30) Priority: 17.01.1997 IT BO970021

(74) Representative:
Modiano, Guido, Dr.-Ing. et al
Modiano & Associati S.r.l.
Via Meravigli, 16
20123 Milano (IT)

(71) Applicant: Orsi, Stefano
Jardin Vitoria Regia 05657080, Sao Paulo-SP
(BR)

(54) Distal terminal element for the stem of a primary hip prosthesis

(57) A distal terminal element (1) for the stem of a primary hip prosthesis (P), which over a short extent is tubular (2) and is affected by at least two radial longitudinal slots (3), which form at least two sectors (4) suitable to be flared outward symmetrically before installation in order to assume preset external dimensions which are greater than those of the stem (16) and substantially correspond to the dimensions of the affected medullary canal (C).



Description

The present invention relates to a distal terminal element for the stem of a primary hip prosthesis of the non-cemented type.

Conventionally, the stems of hip prostheses must be rigidly coupled in the medullary canal of the femur after removing the neck at the upper proximal region and instead they simply need to be stabilized at the lower distal end. In practice, stresses are discharged mostly at the rigidly coupled proximal region, while in the distal region it is simply necessary to avoid small relative movements between the apex of the prosthesis and the bone.

In order to avoid such relative movements in the distal region, sometimes the dimensions of the femoral canal are adapted, by successive reaming operations, to the dimensions of the stem of the prosthesis: this requires a nonbiological and prolonged intervention, increases bleeding and possibly facilitates infections and heterotrophic ossifications.

Another method consists in providing a plurality of prostheses with stems provided with a distal part having different diameters (for example five or six or more diameters), but this entails (since the proximal characteristics of the prosthesis also require the availability of a set of four or five or more different types) the need to have a very large range of sizes, which entails high manufacturing and storage costs.

Modular prostheses are also known which consist of modular components which are mutually assembled before installation; however, this solution entails high costs, some difficulty in assembly and the risk of metallosis due to the various metal to metal couplings.

Components are also known in which an external adapter is applied to the distal end of the stem: said adapter is roughly olive-shaped and axially perforated and can be selected before installation among a plurality of olives having different outside diameters. This solution, however, entails the drawback that the olive, in the course of time, can detach and slip off the stem if the stem has to be removed.

The aim of the present invention is to obviate the above-cited drawbacks of the prior art, i.e., to provide a distal terminal element for the stem of a primary hip prosthesis which does not require particular intensive interventions, can assume different dimensions according to requirements without resorting to a large range of stems, and does not entail the presence of detachable components.

Within the scope of this aim, an object of the present invention is to provide a structure which is simple, relatively easy to provide in practice, safe in use, effective in operation and has a relatively low cost.

This aim, this object and others which will become apparent hereinafter are achieved by a distal terminal element for a stem of a primary hip prosthesis, characterized in that over a short extent it is tubular and is pro-

vided with at least two radial longitudinal slots, which form at least two sectors suitable to be flared outward symmetrically before installation in a medullary canal in order to assume preset external dimensions which are greater than those of the stem and substantially correspond to the dimensions of the affected medullary canal.

Further characteristics and advantages of the present invention will become apparent from the following detailed description of a preferred but not exclusive embodiment of a distal terminal element for the stem of a primary hip prosthesis according to the invention, illustrated only by way of non-limitative example in the accompanying drawings, wherein:

figures 1A and 1B are two perspective views of a distal terminal element for the stem of a primary hip prosthesis, in the condition before and after flaring, respectively;

figure 2 is a schematic side view of a distal terminal element according to the present invention and of a corresponding flaring element;

figure 3 is a schematic side view of a distal terminal element according to the present invention and of a corresponding flaring element which is an alternative to the one shown in figure 2;

figure 4 is a schematic perspective view of a distal terminal element according to the present invention and of a corresponding flaring element which is an alternative to those shown in figures 2 and 3;

figure 5 is a schematic perspective view of a distal terminal element according to the present invention and of a corresponding flaring element which is an alternative to those of figures 2, 3 and 4;

figure 6 is a schematic perspective view of a distal terminal element according to the present invention and of a corresponding flaring element which is an alternative to those shown in figures 2, 3, 4 and 5;

figure 7 is a schematic side view of a prosthesis implanted in a femur;

figure 8 is a schematic perspective view of the set of instruments for measurement and adaptation to the femoral canal before application.

With particular reference to the above figures, the reference numeral 1 generally designates a distal terminal element for the stem of a primary hip prosthesis, generally designated by the reference letter P, according to the invention.

The letter F designates the upper part of the femoral bone, from which the neck has been removed, and the letter C designates the medullary canal, as shown in figure 7.

The present invention relates to the lower distal end of the prosthesis P which, over a short extent (for example 20 millimeters), is tubular, 2, and is affected by at least two radial longitudinal slots 3 (in figures 1A and 1B illustrated by way of example there are four slots, but the

number might also be different) which form at least two sectors 4 (four in the illustrated case).

The sectors 4 are meant to be flared out and widened symmetrically outward, see figure 1B, before the installation of the prosthesis in the femoral bone in order to assume preset outside dimensions which are greater than those of the stem and are substantially equal to those of the medullary canal, which is measured beforehand and optionally treated: advantageously, the edge 5 of the distal end is slightly rounded so as to prevent sharp corners from making contact with the internal cortex of the medullary canal.

The sectors 4 can be flared outward in any manner. Some solutions for performing outward flaring, given merely by way of example, are shown schematically in figures 2, 3, 4, 5 and 6; the ends of the slots are affected by larger holes 7 which are suitable to facilitate the flaring of the sectors 4.

In the example of figure 2, the sectors 4 are plastically deformed by inserting and axially forcing a frustum-shaped tool 6 which can be removed after deformation: the tool 6 is associated with a sturdy lever arm on which one acts manually before installation, after clamping the stem in a pair of supporting jaws: in another embodiment, the tool 6 is associated with the threaded stem of a screw press.

In the embodiment shown in figure 3, the tubular portion 2 extends beyond the slots 3 with a threaded portion 6 in which an end screw 8 of a stem 9 is coupled; the stem ends with a diverging frustum-shaped portion 10; the screw coupling of portions of longer or shorter lengths of the stem produces a more or less extensive flaring of the sectors 4.

According to requirements, the screw can be removed from the stem before insertion in the femoral canal or can remain rigidly coupled to the stem, optionally by deforming the thread of the screw.

In another embodiment, shown in figure 4, the threaded hole 6a in the stem is frustum-shaped and the screw 8a has a conical stem so that it directly opens out the sectors 4 with its body during penetration.

In another embodiment, shown in figure 5, the radial longitudinal slots 3 are thinner proximate to the end, so as to form mutually opposite pairs of coupling teeth 11 which are meant to fit, by snap action, in corresponding notches 12 of a terminal element 13 which is shaped like a star, provided with four arms in the particular case, with wedges 14 which are suitable to be forced axially into the slots 3 of the tubular end of the terminal element in order to flare out the sectors 4. Depending on the larger or smaller dimensions of the outside diameter that the terminal element is to have, star-shaped sets of wedges with more or less deep notches are inserted.

In an alternative embodiment, shown in figure 6, the radial longitudinal slots 3 are shaped like an elongated drop. A terminal element 13a which is shaped like a wedge is provided with surfaces 14a which join at the

vertex of the wedge and are suitable to be forced axially into the slots 3 of the tubular end of the terminal element in order to flare out the sectors 4. Depending on the larger or smaller dimensions of the outside diameter that the terminal element must have, the wedge 13a has a different thickness. Protruding portions 12a are provided in the upper region of the wedge to engage the tubular element 2 when the wedge is inserted in the slots 3.

Figure 7 illustrates the different components of the set of instruments that has been devised for measurement and adaptation to the femoral canal before application: the set of instruments comprises a plurality of specimen balls 15 with increasing diameters, which can be rigidly coupled by screwing to the threaded end of a stem 16, provided with graduation notches, which allows to measure the cross-section of the femoral canal and the relative distance from the upper end of the bone: once the ball that has the same diameter and dimensions as the canal has been located, the ball is fixed to the end of a rasp 17 (chosen among a plurality of increasingly larger rasps) which is shaped so as to allow to act on the proximal end of the bone with the rasp without interfering with the bone in a distal position during the preparation of the seat for the proximal part of the prosthesis; in some cases it may be necessary to widen the femoral canal in the distal region: thereafter, the appropriate ball is replaced at the end of the rasp.

After measuring the diameter of the medullary canal and after preparing the proximal region of the bone according to its anatomy and therefore according to the chosen prosthesis, on the basis of the most suitable proximal size and shape characteristics, the sectors 4 of the stem are flared outward with any method, for example one of those shown in figures 2, 3, 4, 5 and 6, until the outside diameter of the distal end is equal to the diameter of the determined specimen ball: the value of the outside diameter reached by means of the deformation is then checked with a go-not-go system, for example, which is constituted by tubular specimen pipes with increasing diameters: once the prosthesis has been implanted, the distal end is therefore highly stabilized in the medullary canal.

It has thus been shown that the present invention achieves the intended aim and objects and in particular that a distal terminal element for the stem of a primary hip prosthesis has been provided which does not require particularly intensive interventions, can assume different dimensions according to requirements without requiring a wide range of stems (in practice, a single stem for each kind of prosthesis with different proximal characteristics) and does not entail the presence of detachable components.

The invention thus conceived is susceptible of numerous modifications and variations, all of which are within the scope of the inventive concept.

All the details may also be replaced with other technically equivalent ones.

In practice, the materials employed, as well as the shapes and the dimensions, may be any according to requirements without thereby abandoning the scope of the protection of the appended claims.

Where technical features mentioned in any claim 5 are followed by reference signs, those reference signs have been included for the sole purpose of increasing the intelligibility of the claims and accordingly, such reference signs do not have any limiting effect on the interpretation of each element identified by way of example 10 by such reference signs.

Claims

1. A distal terminal element for a stem of a primary hip 15 prosthesis, characterized in that over a short extent it is tubular and is provided with at least two radial longitudinal slots, which form at least two sectors suitable to be flared outward symmetrically before installation in a medullary canal in order to assume 20 preset external dimensions which are greater than those of the stem and substantially correspond to the dimensions of the affected medullary canal.
2. A terminal element according to claim 1, character- 25 ized in that said sectors are deformed plastically by means of the axial insertion and forcing of a removable frustum-shaped tool.
3. A terminal element according to claim 1, character- 30 ized in that said tubular portion is internally threaded for coupling to a screw whose screwing produces the flaring of said sectors.
4. A terminal element according to claim 3, character- 35 ized in that a stem is rigidly coupled to the screw and ends with a diverging frustum-shaped portion.
5. A terminal element according to claim 4, character- 40 ized in that said tubular portion has a frustum-shaped threaded hole and said screw has a conical shank.
6. A terminal element according to claim 3, character- 45 ized in that said screw is removed from the stem before insertion in the femoral canal.
7. A terminal element according to claim 1, character- 50 ized in that said radial longitudinal slots, proximate to the distal end, become narrower so as to form teeth for coupling at corresponding notches of a terminal element which is shaped like a star with wedges which are suitable to be forced axially into said tubular end in order to flare out said sectors. 55
8. A terminal element according to claim 1, character- ized in that the ends of said slots are affected by 60 holes which have an enlarged diameter and are

suitable to facilitate the flaring out of said sectors.

9. A set of instruments for measurement and adapta- 65 tion to a femoral canal before application of a terminal element according to claim 1, comprising a plurality of balls of increasing diameter which can be rigidly coupled to the end of a graduated stem for measuring the femoral canal and to the end of rasps which are shaped so as to not interfere with the bone in the distal position during the prepara- 70 tion of the seat in a proximal position.

FIG.1A




FIG.1B




FIG.2




FIG.3







FIG. 4








FIG. 7





FIG. 8



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 853 931 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
17.03.1999 Bulletin 1999/11

(51) Int. Cl.⁶: **A61F 2/36**, **B21D 41/02**,
A61F 2/46

(43) Date of publication A2:
22.07.1998 Bulletin 1998/30

(21) Application number: **97122707.9**

(22) Date of filing: **22.12.1997**

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **17.01.1997 IT BO970021**

(71) Applicant: **Orsi, Stefano**
Jardin Vitoria Regia 05657080, Sao Paulo-SP
(BR)



(72) Inventor: **Orsi, Stefano**
Jardin Vitoria Regia 05657080, Sao Paulo-SP
(BR)

(74) Representative:
Modiano, Guido, Dr.-Ing. et al
Modiano & Associati SpA
Via Meravigli, 16
20123 Milano (IT)

(54) **Distal terminal element for the stem of a primary hip prosthesis**

(57) A distal terminal element (1) for the stem of a primary hip prosthesis (P), which over a short extent is tubular (2) and is affected by at least two radial longitudinal slots (3), which form at least two sectors (4) suitable to be flared outward symmetrically before

installation in order to assume preset external dimensions which are greater than those of the stem (16) and substantially correspond to the dimensions of the affected medullary canal (C).





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 97 12 2707

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	EP 0 280 642 A (BUSE) 31 August 1988	1	A61F2/36 B21D41/02 A61F2/46
Y	* column 3, line 45 - line 59; claim 7; figure *	2,3,8	
Y	US 4 198 711 A (ZEIBIG) 22 April 1980 * the whole document *	2,3	
Y	US 5 258 035 A (HOFMANN) 2 November 1993 * column 2, line 44 - column 4, line 16; figures 1-9,13 *	8	
A	FR 2 483 218 A (CUILLERON) 4 December 1981 * the whole document *	1,8	
X	DE 34 26 947 A (BUSE) 12 December 1985 * page 9, line 33 - page 10, line 6; figure 1 *	1	
Y	US 5 569 263 A (HEIN) 29 October 1996 * the whole document *	9	
Y	US 5 342 366 A (WHITESIDE) 30 August 1994 * the whole document *	9	
A	US 5 002 578 A (LUMAN) 26 March 1991 * column 7, line 11 - line 13; figure 6 *	1	
A	US 4 772 286 A (GOBLE) 20 September 1988 * column 8, line 38 - column 9, line 6; figures 5A,5B *	2,3	
A	EP 0 385 930 A (GEBRÜDER SULZER) 5 September 1990 * column 2, line 44 - line 52; figures 1,2 *	2,4	TECHNICAL FIELDS SEARCHED (Int.Cl.6) A61F B21D
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
THE HAGUE		15 January 1999	Klein, C
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03 82 (P/4C1)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 97 12 2707

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	EP 0 477 076 A (LA CELLULOSE DU PIN) 25 March 1992 * column 3, line 25 - column 5, line 3; figures 1-3 *	3,5	
A	US 5 549 702 A (RIES) 27 August 1996 * figures 2,4 *	5	
A	US 5 554 192 A (CROWNINSHIELD) 10 September 1996 * the whole document *	7	
A	US 3 815 590 A (DEYERLE) 11 June 1974 * the whole document *	9	
A	WO 92 03993 A (PFIZER HOSPITAL PRODUCTS GROUP) 19 March 1992	9	
A	EP 0 543 099 A (BRISTOL-MYERS SQUIBB COMPANY) 26 May 1993		
A	FR 2 591 885 A (MAI) 26 June 1987		
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
Place of search THE HAGUE		Date of completion of the search 15 January 1999	Examiner Klein, C
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/92 (P04C01)



European Patent
Office

Application Number

EP 97 12 2707

CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☒ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:



European Patent
Office

**LACK OF UNITY OF INVENTION
SHEET B**

Application Number

EP 97 12 2707

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. Claims: 1-8

A distal terminal element for a stem of a primary hip prosthesis comprising a tubular portion provided with radial longitudinal slots forming sectors suitable to be flared outward symmetrically

2. Claim : 9

A set of instruments for measurement and adaptation to a femoral canal comprising a plurality of balls of increasing diameter which can be coupled to the end of a graduated stem and to the end of rasps

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 12 2707

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

15-01-1999

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP 280642	A	31-08-1988	DE	3701198 A	28-07-1988
US 4198711	A	22-04-1980	DE	2646478 A	20-04-1978
			AT	344310 B	10-07-1978
			AT	868476 A	15-11-1977
			CH	607747 A	31-10-1978
			FR	2367480 A	12-05-1978
			GB	1585672 A	11-03-1981
			JP	53049891 A	06-05-1978
			SE	415322 B	29-09-1980
			SE	7613205 A	15-04-1978
			US	4268919 A	26-05-1981
US 5258035	A	02-11-1993	US	5480452 A	02-01-1996
FR 2483218	A	04-12-1981	NONE		
DE 3426947	A	12-12-1985	AU	4493085 A	10-01-1986
			BR	8506770 A	23-09-1986
			WO	8600011 A	03-01-1986
			DK	56486 A	05-02-1986
			EP	0183809 A	11-06-1986
			JP	61502308 T	16-10-1986
US 5569263	A	29-10-1996	NONE		
US 5342366	A	30-08-1994	NONE		
US 5002578	A	26-03-1991	NONE		
US 4772286	A	20-09-1988	CA	1336058 A	27-06-1995
			AU	606949 B	21-02-1991
			AU	1618288 A	16-11-1995
			EP	0342281 A	23-11-1989
			US	RE34293 E	22-06-1993
EP 385930	A	05-09-1990	CH	677442 A	31-05-1991
EP 477076	A	25-03-1992	FR	2666736 A	20-03-1992
US 5549702	A	27-08-1996	NONE		
US 5554192	A	10-09-1996	NONE		
US 3815590	A	11-06-1974	NONE		

EPO FORM P0439

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 12 2707

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

15-01-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9203993 A	19-03-1992	US 5100407 A	31-03-1992
		AT 114956 T	15-12-1994
		CA 2089734 A,C	05-03-1992
		DE 9190125 U	29-04-1993
		DE 69105739 D	19-01-1995
		DE 69105739 T	27-04-1995
		DK 548109 T	06-03-1995
		EP 0548109 A	30-06-1993
		ES 2065056 T	01-02-1995
		IE 65275 B	18-10-1995
		IL 99334 A	31-07-1995
		JP 8017788 B	28-02-1996
		JP 6500026 T	06-01-1994
		PT 98847 A	31-01-1994
EP 543099 A	26-05-1993	AU 659195 B	11-05-1995
		AU 2219992 A	20-05-1993
		CA 2078818 A	20-05-1993
		JP 5208028 A	20-08-1993
		US 5507829 A	16-04-1996
		US 5702482 A	30-12-1997
FR 2591885 A	26-06-1987	EP 0229578 A	22-07-1987
		US 4756711 A	12-07-1988

